

Thank you for purchasing Happy Trails products. Our products are proudly hand made in Boise Idaho, USA. If you have any questions or concerns about the installation of this product, please contact us directly at 1-800-444-8770 or e-mail installation@happy-trail.com.

Before you begin, place the bike on a hard level surface where you have room to work. Lay out the parts included in this kit and compare to the parts list of these instructions. If any parts or hardware are missing, contact us immediately at the number listed above.

When installing HT guards and racks, <u>leave all</u> <u>bolts loose until entire rack is fitted</u>. This allows the rack to move and take up differences in frame construction.

We also recommend that removable strength thread locking compound be used on all threaded connections.




## Installation:

Remove the upper passenger peg bracket mounting bolt. Remove the turn signals taking care not to damage wires.

Mount the SU racks one side at a time starting with the top mount. Thread in the M6x75 bolt through the SU rack and the turn signal relocation tab. Use this tab ONLY if no top rack is being used.





Install the turn signals into the bracket. The wires may need to be lengthened. If a top rack is used, mount the turn signals in the holes provided in the uprights.



## **Bolt List:**

- 2 M8x50 SHCS2 M6x75 SHCS
- 4 M6x16 SHCS
- 4 6mm Nylock nuts
- 10 1/4 Washers

## These items are not used with a tail rack:

- 5/16 Washers
- 8mm Nylock nutsM8x25 SHCS
- 2 Short turn signal
  - tabs

## OF F

**Happy Trails Products**