

Kawasaki Concours

Installation and Hardware list

Installation of SU Racks

1. Remove stock mounts from each side. Loosen passenger pegs from frame. Remove seat. Remove turn signals from bike.
2. Install racks, and bumper. Start all bolts loosely at first then tighten when all are in place.
3. Remove turn signals from plastic housing by removing the nut on the end. See turn signal assembly diagram attached.
4. Place turn signals in Happy Trails cross over bracket, using nut and washer on the end of the turn signal stem and tighten. Cross over bracket mounts above the license plate with supplied hardware.

Hardware List:

Qty.	Size	Location
2	6 x 30mm bolts	Bumper
2	6mm nylock nuts	Bumper
4	1/4 washer	Bumper
4	8 x 45mm bolts	Top Mounts
2	8 x 65mm bolts	Foot Pegs
2	8mm nylock nuts	Foot Pegs
2	5/16 washer	Foot Peg
2	5/16 washers	Turn Signal mount
2	6 x 16mm bolts	Turn Signal mount
4	1/4 washers	Turn Signal mount
2	6mm nylock nuts	Turn Signal mount
4	3/4 spacers	
1	crossover bracket	

Happy Trails Products

Red-Nine, Inc.
4545 W. Chinden Blvd.
Boise, Id 83714

Order Line: 800-444-8770
Phone: 208-377-8771
Fax: 208-377-8772
Todd.rumps@happy-trail.com



HAPPY-TRAIL.COM



Turn Signal Assembly Diagram

