

Thank you for purchasing Happy Trails products. Our products are proudly hand made in Boise Idaho, USA. If you have any questions or concerns about the installation of this product, please contact us directly at 1-800-444-8770 or e-mail installation@happy-trail.com.

Before you begin, place the bike on a hard level surface where you have room to work. Lay out the parts included in this kit and compare to the parts in these instructions. If any parts or hardware are missing, contact us immediately at the number listed above.

Disassembly

Remove the turn signals from their locations.

Installation

Mount the side brackets to the angle brackets using the M8 button head bolts, nuts and flat washers. Tighten just enough to allow movement with some force.

Mount the side plates on the bike according to the photo at the right using the 4 M8x20 SHCS bolts and flat washers.

Set the top plate on the mounts and position to your liking. Mark the hole locations and drill 3/8" holes in the top plate. Use the remaining M8 button head bolts to mount the top plate to the mounts.

Position to your liking and tighten up all bolts.

IMPORTANT!!!!

When installing Happy Trails products, leave all bolt connections loose until the entire product is installed. Then go back and tighten all connections. We recommend the use of thread locking compound.









Turn Signal Relocation

Mount the turn signal bracket to the upper license plate mount and then mount the turn signals to this bracket. Turn signal wires may need to be lengthened to reach the connectors.

Bolt List:

- 4 M8x20 SHCS
- 20 5/16 FLAT WASHERS
- 8 M8x20 BUTTON HEAD BOLTS
- 8 8MM NYLOCK NUTS

Parts List:

TOP PLATE 2 ANGLE BRACKETS 2 SIDE PLATES TURN SIGNAL BRACKET



10/14/13 Rev. 2 JE HTP9-1-7-20