

Buell Ulysses

Install Instructions:

Tail Rack & Plate

*A removable thread lock is recommended

1. Remove stock tail rack and back rest. Remove the 2 bolts under the seat, shown in **pic #1**. Using the 1/4" x 1" bolts attach the flat bar to the bike.
2. Place the tail rack support on the bike as seen in **pic #2** using the 8 x 25mm bolts. Start the bolts to the rear most
3. Attach the tail plate support to the flat bar using the 6 x 30mm bolts and 8mm nuts.
4. Place the tail plate in desired location and mark the four attachment hols, drill the plate using

- a 1/4" drill bit, Attach the tail plate with the four 6 x 20 BH bolts and washers to the tail plate support as seen in **pic #3**.
5. Tighten all bolts.

Hardware List:

Bolt list

3/16" washers - 4
tail plate to tail plate support

6x20mm bh bolts - 4
tail plate to tail plate support

8x25mm bolts - 2
Tail plate support to bike

1/4x1" bolts - 2
Flat bar to frame

6x30mm bolts - 2
Tail plate support to flat bar

6mm nylock nuts 2
Tail plate support to flat bar

3/16" washers - 2
Tail plate support to

Included in kit

T-3 Top plate 1

Tube tail rack base 1

Bolt kit 1

Flat mounting bar 1
with 4 slots

